


AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Original) A method of treating a subterranean formation comprising:
providing a gelled liquid hydrocarbon treatment fluid comprising a liquid hydrocarbon and a gelling agent that comprises a polyvalent metal salt of an organophosphonic acid ester or a polyvalent metal salt of an organophosphonic acid, and
treating the subterranean formation with the gelled liquid hydrocarbon treatment fluid.
2. (Currently Amended) The method of claim 1 wherein the gelled liquid hydrocarbon treatment fluid further comprises one element selected from the group consisting of water and/or a base bases, and combinations thereof.
3. (Currently Amended) The method of claim 1 wherein the liquid hydrocarbon ~~comprises an α -olefin, an internal olefin, an alkane, an aromatic solvent, a cycloalkane, liquefied petroleum gas, kerosene, diesel oil, gas oil, fuel oil, a petroleum distillate, a crude oil mixture, or a mixture thereof~~ is selected from the group consisting of α -olefins, internal olefins, alkanes, aromatic solvents, cycloalkanes, liquefied petroleum gases, kerosene, diesel oil, gas oil, fuel oil, petroleum distillates, crude oil mixtures, and mixtures thereof.
4. (Original) The method of claim 1 wherein the liquid hydrocarbon is designed for use with CO₂.
5. (Original) The method of claim 1 wherein the polyvalent metal salt of an organophosphonic acid ester is formed by a metathesis reaction comprising an alkali metal or an ammonium salt of the organophosphonic acid ester.
6. (Original) The method of claim 1 wherein the polyvalent metal salt of an organophosphonic acid ester is formed by a metathesis reaction comprising an organophosphonic acid dialkyl ester.
7. (Currently Amended) The method of claim 1 wherein the polyvalent metal salt of an organophosphonic acid ester is formed from the reaction of an activator composition that comprises a source of polyvalent metal ions and an organophosphonic acid ester, the organophosphonic acid ester having the formula:



wherein R or R' comprises a hydrocarbon group having about 1 to about 30 carbon atoms that, ~~for example, may comprise~~ comprises a linear or branched alkyl, alkenyl, aryl, alkylaryl, arylalkyl, cycloalkyl, alkyl ether, aryl ether, alkyl aryl ether, or a mixture thereof; and R or R' comprises a hydrocarbon group having from about 1 to about 6 carbon atoms.


8. (Currently Amended) The method of claim 7 wherein the polyvalent metal ions ~~comprise aluminum ions, gallium ions, lanthanum ions, ruthenium ions, iron ions, or lanthanide rare earth series ions~~ are selected from the group consisting of aluminum ions, gallium ions, lanthanum ions, ruthenium ions, iron ions, lanthanide rare earth series ions, and combinations thereof.

9. (Original) The method of claim 7 wherein the polyvalent metal ions comprise ions having a +3 oxidation state.

10. (Currently Amended) The method of claim 7 wherein the activator composition ~~comprises a ferric iron salt, aluminum chloride, sodium aluminate, or aluminum isopropoxide~~ is selected from the group consisting of ferric iron salts, aluminum chloride, sodium aluminate, aluminum isopropoxide, and combinations thereof.

11. (Original) The method of claim 1 wherein the polyvalent metal salt of an organophosphinic acid is formed by a metathesis reaction comprising an organophosphinic acid alkyl ester.

12. (Currently Amended) The method of claim 1 wherein the polyvalent metal salt of an organophosphinic acid is formed from a reaction of an activator composition that comprises a source of polyvalent metal ions and an organophosphinic acid, the organophosphinic acid having the formula:



wherein R¹ or R² comprises a hydrocarbon group having about 1 to about 30 carbon atoms that, ~~for example, may comprise~~ comprises a linear or branched alkyl, alkenyl, aryl, alkylaryl,

arylalkyl, cycloalkyl, alkyl ether, aryl ether, alkyl aryl ether, or a mixture thereof; and R^1 or R^2 comprises a hydrocarbon group having from about 1 to about 6 carbon atoms.

13. (Currently Amended) The method of claim 12 wherein the source of polyvalent metal ions ~~comprises aluminum ions, gallium ions, lanthanum ions, ruthenium ions, iron ions, or lanthanide rare earth series ions~~ is selected from the group consisting of aluminum ions, gallium ions, lanthanum ions, ruthenium ions, iron ions, lanthanide rare earth series ions, and combinations thereof.

14. (Original) The method of claim 12 wherein the polyvalent metal ions comprise ions having a +3 oxidation state.

15. (Original) The method of claim 1 wherein the gelled liquid hydrocarbon treatment fluid comprises a surfactant.

16. (Currently Amended) The method of claim 15 wherein the surfactant ~~comprises imidazoline, a fatty acid soap, a fatty acid, dioctyl sulphosuccinate, sodium alkyl benzene sulphonate, a fatty acid ester, a fatty acid alkanolamide, or an amido betaine~~ is selected from the group consisting of imidazoline, fatty acid soaps, fatty acids, dioctyl sulphosuccinate, sodium alkyl benzene sulphonate, fatty acid esters, fatty acid alkanolamides, amido betaines, and combinations thereof.

17. (Original) The method of claim 15 wherein the surfactant is present in the gelled liquid hydrocarbon treatment fluid in an amount in the range of from about 0.1% to about 10% based on the gelling agent.

18. (Original) The method of claim 1 wherein the gelled liquid hydrocarbon treatment fluid comprises an enhancer.

19. (Original) The method of claim 18 wherein the enhancer provides at least some alkalinity to the gelled liquid hydrocarbon treatment fluid.

20. (Original) The method of claim 18 wherein the enhancer has the general formula $C_nH_mO_xN_y$, wherein n is from about 1 to about 50, m is from about 0 to about the number necessary to satisfy the valence of the enhancer, x is from about 1 to about 10, and y is from about 0 to about 10.

21. (Currently Amended) The method of claim 18 wherein the enhancer ~~comprises an ethoxylated amine, triethanolamine, N,N-dibutyl ethanol amine, an oxyalkylated di-C₂-C₈-alkyl amine, N,N-di-loweralkyl fatty amine, an oxyalkylated fatty amine, monoammonium citrate, bis(hydroxyethyl)-tallowamine, ethoxylated dehydroabietylamine, or a mixture thereof~~ is

selected from the group consisting of ethoxylated amines, triethanolamine, *N,N*-dibutyl ethanol amine, oxyalkylated di-C₂-C₈-alkyl amines, *N,N*-di-loweralkyl fatty amine, oxyalkylated fatty amines, monoammonium citrate, bis(hydroxyethyl) tallowamine, ethoxylated dehydroabietylamine, and mixtures thereof.

22. (Original) The method of claim 1 wherein treating the subterranean formation involves fracturing a portion of the subterranean formation.

23. (Original) The method of claim 22 wherein the gelled liquid hydrocarbon treatment fluid comprises proppant.

24. (Original) The method of claim 1 wherein treating the subterranean formation involves providing sand control to at least a portion of the subterranean formation.

25. (Original) The method of claim 24 wherein the gelled liquid hydrocarbon treatment fluid comprises gravel.

26. (Currently Amended) The method of claim 23 or 25 wherein the proppant or gravel ~~comprise nut shells, resin-coated nut shells, graded sand, resin-coated sand, sintered bauxite, particulate ceramic materials, glass beads, or particulate polymeric materials~~ is selected from the group consisting of nut shells, resin-coated nut shells, graded sand, resin-coated sand, sintered bauxite, particulate ceramic materials, glass beads, particulate polymeric materials, and combinations thereof.

27. (Original) The method of claim 1 wherein the gelled liquid hydrocarbon treatment fluid comprises water, the water being present in an amount of at least about 0.05% by the total treatment fluid volume.

28. (Original) The method of claim 1 wherein the gelled liquid hydrocarbon treatment fluid further comprises a breaker, the breaker being present in an amount sufficient to reduce the viscosity of the gelled liquid hydrocarbon treatment fluid at a desired time.

29. (Original) The method of claim 28 wherein the breaker comprises a delayed gel breaker.

30. (Original) The method of claim 29 wherein the delayed gel breaker comprises an encapsulated delayed gel breaker.

31. (Original) The method of claim 29 wherein the delayed gel breaker is present in an amount in the range of from about 0.01% to about 3% w/v.

32. (Currently Amended) The method of claim 28 wherein the breaker ~~comprises hard-burned magnesium oxide, an alkali-metal carbonate, alkali-metal bicarbonate, alkali-metal~~

~~acetate, an alkaline earth metal oxides, an alkali metal hydroxide, an amine, or a weak acid is~~
selected from the group consisting of hard burned magnesium oxide, alkali metal carbonates,
alkali metal bicarbonate, alkali metal acetate, alkaline earth metal oxides, alkali metal
hydroxides, amines, weak acids, and combinations thereof.

33. (Original) The method of claim 28 wherein the breaker comprises a reducing agent that is capable of reducing ferric iron to ferrous iron.

34. (Currently Amended) The method of claim 33 wherein the reducing agent ~~comprises~~ is selected from the group consisting of stannous chloride, thioglycolic acid, hydrazine sulfate, sodium diethyldithiocarbamate, sodium dimethyldithiocarbamate, sodium hypophosphite, potassium iodide, hydroxylamine hydrochloride, 2-mercaptoethanol, ascorbic acid, sodium thiosulfate, sodium dithionite, ~~or~~ sodium sulfite, and combinations thereof.

35. (Original) The method of claim 28 wherein the breaker is present in an amount of 0.01% to about 3% of the volume of the treatment fluid.

36. (Original) The method of claim 1 wherein the treating the subterranean formation involves using the gelled liquid hydrocarbon treatment fluid to provide a plugging agent to a portion of the subterranean formation or a portion of a well bore penetrating the subterranean formation.

37. (Original) The method of claim 1 wherein treating the subterranean formation involves using the gelled liquid hydrocarbon treatment fluid as a well bore cleanup fluid.

38. (Original) The method of claim 1 wherein treating the subterranean formation involves using the gelled liquid hydrocarbon treatment fluid to perform a viscous sweep of a portion of the subterranean formation or a portion of a well bore penetrating the subterranean formation.

39. (Original) The method of claim 1 wherein treating the subterranean formation involves insulating a portion of the subterranean formation, a portion of a well bore penetrating the subterranean formation, or a tubing placed in a well bore penetrating the subterranean formation.

40. (Original) The method of claim 1 further comprising the step of preparing the gelled liquid hydrocarbon treatment fluid at the location of the subterranean formation.

41. (Original) The method of claim 1 further comprising the step of preparing the gelled liquid hydrocarbon treatment fluid at a location away from the subterranean formation and transporting the gelled liquid hydrocarbon treatment fluid to the subterranean formation.

42. (Original) A method of fracturing a portion of a subterranean formation comprising:

providing a gelled liquid hydrocarbon fracturing fluid comprising a gelling agent that comprises a polyvalent metal salt of an organophosphonic acid ester or a polyvalent metal salt of an organophosphinic acid, and

contacting the portion of the subterranean formation with the gelled liquid hydrocarbon fracturing fluid under conditions effective to create or enhance at least one fracture in the subterranean formation.

43. (Currently Amended) The method of claim 42 wherein the gelled liquid hydrocarbon fracturing fluid further comprises one element selected from the group consisting of water and/or a base bases, and combinations thereof.

44. (Currently Amended) The method of claim 42 wherein the gelled liquid hydrocarbon fracturing fluid ~~comprises an α -olefin, an internal olefin, an alkane, an aromatic solvent, a cycloalkane, liquefied petroleum gas, kerosene, diesel oil, gas oil, fuel oil, a petroleum distillate, a crude oil mixture, or a mixture thereof~~ is selected from the group consisting of α -olefins, internal olefins, alkanes, aromatic solvents, cycloalkanes, liquefied petroleum gas, kerosene, diesel oil, gas oil, fuel oil, petroleum distillates, crude oil mixtures, and combinations thereof.

45. (Original) The method of claim 42 wherein the polyvalent metal salt of an organophosphonic acid ester or the polyvalent metal salt of an organophosphinic acid is present in an amount in the range of from about 0.1% to about 10% w/v.


46. (Original) The method of claim 42 wherein the polyvalent metal salt of an organophosphonic acid ester or the polyvalent metal salt of an organophosphinic acid is present in an amount in the range of from about 0.2% to about 5% w/v.

47. (Original) The method of claim 42 wherein the polyvalent metal salt of an organophosphonic acid ester is formed by a metathesis reaction comprising an alkali metal or an ammonium salt of the organophosphonic acid ester.

48. (Original) The method of claim 42 wherein the polyvalent metal salt of an organophosphonic acid ester is formed by a metathesis reaction comprising an organophosphonic acid dialkyl ester.

49. (Currently Amended) The method of claim 42 wherein the polyvalent metal salt of an organophosphonic acid ester is formed from the reaction of an activator composition that


comprises a source of polyvalent metal ions and an organophosphonic acid ester, the organophosphonic acid ester having the formula:



wherein R or R' comprises a hydrocarbon group having about 1 to about 30 carbon atoms that, ~~for example, may comprise~~ comprises a linear or branched alkyl, alkenyl, aryl, alkylaryl, arylalkyl, cycloalkyl, alkyl ether, aryl ether, alkyl aryl ether, or a mixture thereof; and R or R' comprises a hydrocarbon group having from about 1 to about 6 carbon atoms.

50. (Original) The method of claim 49 wherein the polyvalent metal ions comprise ions having a +3 oxidation state.


51. (Original) The method of claim 42 wherein the polyvalent metal salt of an organophosphonic acid ester is formed from the reaction of an activator composition that comprises a source of polyvalent metal ions and an organophosphonic acid ester, the organophosphonic acid ester having the formula:



where R represents a hydrocarbon group having the general formula $\text{C}_n\text{H}_{2n+1}$, where n is from about 3 to about 21.

52. (Original) The method of claim 42 wherein the polyvalent metal salt of an organophosphonic acid is formed by a metathesis reaction comprising an organophosphonic acid alkyl ester.


53. (Currently Amended) The method of claim 42 wherein the polyvalent metal salt of an organophosphonic acid is formed from a reaction of an activator composition that comprises a source of polyvalent metal ions and an organophosphonic acid, the organophosphonic acid having the formula:



wherein R¹ or R² comprises a hydrocarbon group having about 1 to about 30 carbon atoms that, ~~for example, may comprise~~ comprises a linear or branched alkyl, alkenyl, aryl, alkylaryl, arylalkyl, cycloalkyl, alkyl ether, aryl ether, alkyl aryl ether, or a mixture thereof; and R¹ or R² comprises a hydrocarbon group having from about 1 to about 6 carbon atoms.

54. (Original) The method of claim 53 wherein the source of polyvalent metal ions comprise ions having a +3 oxidation state.

55. (Original) The method of claim 42 wherein the polyvalent metal salt of an organophosphinic acid is formed from a reaction of an activator composition comprising a source of polyvalent metal ions and an organophosphinic acid, the organophosphinic acid having the formula:



where R represents a linear or branched alkyl chain having the general formula C_nH_{2n+1}, where n is from about 3 to about 21.

56. (Original) The method of claim 42 wherein the gelled liquid hydrocarbon treatment fluid comprises an enhancer.

57. (Original) The method of claim 42 wherein the gelled liquid hydrocarbon treatment fluid comprises a surfactant.

58. (Original) The method of claim 56 has the general formula C_nH_mO_xN_y, wherein n is about 1 to about 50, m is about 0 to about the number necessary to satisfy the valence of the enhancer, x is about 1 to about 10, and y is about 0 to about 10.

59. (Original) The method of claim 42 wherein the gelled liquid hydrocarbon fracturing fluid comprises proppant.

60. (Original) The method of claim 58 wherein the proppant is present in an amount in the range of from about 1 to about 32 pounds of proppant per gallon of treatment fluid.

61. (Currently Amended) The method of claim 59 wherein the proppant ~~comprises nut shells, resin-coated nut shells, graded sand, resin-coated sand, sintered bauxite, particulate ceramic materials, glass beads, or particulate polymeric materials~~ is selected from the group consisting of nut shells, resin coated nut shells, graded sand, resin-coated sand, sintered bauxite, particulate ceramic materials, glass beads, particulate polymeric materials, and combinations thereof.

62. (Original) The method of claim 42 wherein the gelled liquid hydrocarbon fracturing fluid further comprises a breaker, the breaker being present in an amount sufficient to reduce the viscosity of the gelled liquid hydrocarbon treatment fluid at a desired time.

63. (Original) The method of claim 62 wherein the breaker is present in an amount of about 0.01% to about 3% w/v.

64. (Original) A method of providing sand control to a portion of a subterranean formation comprising:

providing a gelled liquid hydrocarbon gravel pack fluid that comprises gravel particulates and a gelling agent that comprises a polyvalent metal salt of an organophosphonic acid ester or a polyvalent metal salt of an organophosphinic acid; and

contacting the portion of the subterranean formation with the gelled liquid hydrocarbon gravel pack fluid so as to form a gravel pack near the portion of the subterranean formation.

65. (Currently Amended) The method of claim 64 wherein the gelled liquid hydrocarbon gravel pack fluid further comprises one element selected from the group consisting of water and/or a base bases, and combinations thereof.

66. (Currently Amended) The method of claim 64 wherein the gelled liquid hydrocarbon gravel pack fluid ~~comprises an α -olefin, an internal olefin, an alkane, an aromatic solvent, a cycloalkane, liquefied petroleum gas, kerosene, diesel oil, gas oil, fuel oil, a petroleum distillate, a crude oil mixture, or a mixture thereof~~ is selected from the group consisting of α -olefins, internal olefins, alkanes, aromatic solvents, cycloalkanes, liquefied petroleum gas, kerosene, diesel oil, gas oil, fuel oil, petroleum distillates, crude oil mixtures, and mixtures thereof.


67. (Original) The method of claim 64 wherein the polyvalent metal salt of an organophosphonic acid ester or the polyvalent metal salt of an organophosphinic acid are present in an amount in the range of from about 0.1% to about 10% w/v.

68. (Original) The method of claim 64 wherein the polyvalent metal salt of an organophosphonic acid ester or the polyvalent metal salt of an organophosphinic acid are present in an amount in the range of from about 0.1% to about 5% w/v.

69. (Original) The method of claim 64 wherein the polyvalent metal salt of an organophosphonic acid ester is formed by a metathesis reaction comprising an alkali metal or an ammonium salt of the organophosphonic acid ester.

70. (Original) The method of claim 64 wherein the polyvalent metal salt of an organophosphonic acid ester is formed by a metathesis reaction comprising an organophosphonic acid dialkyl ester.


71. (Currently Amended) The method of claim 64 wherein the polyvalent metal salt of an organophosphonic acid ester is formed from the reaction of an activator composition that comprises a source of polyvalent metal ions and an organophosphonic acid ester, the organophosphonic acid ester having the formula:



wherein R or R' comprises a hydrocarbon group having about 1 to about 30 carbon atoms that, ~~for example, may comprise~~ comprises a linear or branched alkyl, alkenyl, aryl, alkylaryl, arylalkyl, cycloalkyl, alkyl ether, aryl ether, alkyl aryl ether, or a mixture thereof; and R or R' comprises a hydrocarbon group having from about 1 to about 6 carbon atoms.

72. (Original) The method of claim 71 wherein the polyvalent metal ions comprise ions having a +3 oxidation state.


73. (Original) The method of claim 64 wherein the polyvalent metal salt of an organophosphonic acid ester is formed from the reaction of an activator composition that comprises a source of polyvalent metal ions and an organophosphonic acid ester, the organophosphonic acid ester having the formula:



where R represents a hydrocarbon group having the general formula $\text{C}_n\text{H}_{2n+1}$, where n is from about 3 to about 21.

74. (Original) The method of claim 64 wherein the polyvalent metal salt of an organophosphinic acid is formed by a metathesis reaction comprising an organophosphinic acid alkyl ester.


75. (Currently Amended) The method of claim 64 wherein the polyvalent metal salt of an organophosphinic acid is formed from a reaction of an activator composition that comprises a source of polyvalent metal ions and an organophosphinic acid, the organophosphinic acid having the formula:



wherein R^1 or R^2 comprises a hydrocarbon group having about 1 to about 30 carbon atoms that, ~~for example, may comprise~~ comprises a linear or branched alkyl, alkenyl, aryl, alkylaryl, arylalkyl, cycloalkyl, alkyl ether, aryl ether, alkyl aryl ether, or a mixture thereof; and R^1 or R^2 comprises a hydrocarbon group having from about 1 to about 6 carbon atoms.

76. (Original) The method of claim 75 wherein the source of polyvalent metal ions comprise ions having a +3 oxidation state.

77. (Original) The method of claim 64 wherein the polyvalent metal salt of an organophosphinic acid is formed from a reaction of an activator composition comprising a source of polyvalent metal ions and an organophosphinic acid, the organophosphinic acid having the formula:



where R represents a linear or branched alkyl chain having the general formula $\text{C}_n\text{H}_{2n+1}$, where n is from about 3 to about 21.

78. (Original) The method of claim 64 wherein the gelled liquid hydrocarbon gravel pack fluid comprises an enhancer.

79. (Original) The method of claim 64 wherein the gelled liquid hydrocarbon gravel pack fluid comprises a surfactant.

80. (Original) The method of claim 78 wherein the enhancer has the general formula $\text{C}_n\text{H}_m\text{O}_x\text{N}_y$, wherein n is about 1 to about 50, m is about 0 to about the number necessary to satisfy the valence, x is about 1 to about 10, and y is about 0 to about 10.

81. (Original) The method of claim 64 wherein the gravel is present in an amount in the range of from about 1 to about 32 pounds of gravel per gallon of treatment fluid.

82. (Original) The method of claim 64 wherein the gelled liquid hydrocarbon gravel pack fluid further comprises a breaker, the breaker being present in an amount sufficient to reduce the viscosity of the gelled liquid hydrocarbon treatment fluid at a desired time.

83. (Original) The method of claim 82 wherein the breaker is present in an amount of about 0.01% to about 3% w/v.

84. - 142. (Cancelled)